

ULTIMA RZ6 SET UP SHEET



Name Jyuriya Kajiwara Date 2016/8/21 Truck / City YatabeArena Event Kanto qualifying (Astro)

Front Suspension:

Shock Position:

Upper Spacer: 1 mm

4.8mm Ball Stud:
 UM128(Std.)
 UMW508(+2mm High Mount)

4.8mm Ball Stud Spacer: 1 mm

Camber: 2 °
 - +

AL. Steering Support:
 None
 UMW724

4.8mm Ball Stud:
 LA246 (-1mm Low Mount)
 97050M (Std)

Ackerman Steer Spacer: 1 mm

Ackerman arrow direction:
 Front(std) Rear

Option:
 UMW701 Alu ST Plate
 UMW702 Alu Clank Arm

Bump Steer Spacer: 0 mm

Wheel Hub:
 UM569 / Std
 UM506

4.8mm Ball Stud:

Axle Spacer:
 Out 1 mm
 In 2 mm

Wheel Hub:
 UM569 / Std
 UM506

Axle Height Spacer: 1.5 mm

Toe: In Out 1 °

Tie Rod: _____

Front Bulkhead Weight Placement:
 None
 Bulkhead Inside ___ 9
 On the skid plate ___ 9

Caster:
 25°
 30°

Spacer:
 0.5
 1.0
 None

Caster Block:
 0°
 2°
 4°

Caster Block Position:
 IN (wide/Std)
 OUT (Narrow)

Comments: _____

Wheelbase: F: 1 mm R: - mm

Rear Suspension:

Shock Position:

Upper Arm Position:

4.8mm Ball Stud:
 97050M(Std)
 UM129

Upper Spacer: 2 mm

Hub Carrier:
 Type-B (UM519)
 Type-B2 (UM519-2)

Wing Stay Position:

Shock Stay Type:
 LA352(std)
 LAW59 (Carbom/2mmLow)

Sus.Arm:
 LA272(std)
 UM713B

Camber: 2 °
 - +

Wheelbase: Front: 2 mm, 4 mm, 0 mm, 0 mm

Lower Sus Holder Block:
 Front A Rear Out E

Lower Sus Holder Spacer:
 Front 0.5 mm Rear ___ mm

Toe In: 2.5 °

Sway Bar:
 None
 1.4 mm

UM713B

1.5 mm

Comments: _____

Rear Diff: AXON
 Gear Diff. (Oil:# 5000)
 (Oil weight: 1.1 g)
 Ball Diff.

Shock:

Shock Piston:	Front <u>1.6x2</u>	Rear <u>1.6x2</u>
Shock Oil:	Front <u>#AXON 50</u>	Rear <u>#AXON 45</u>
Shock Spring:	Front <u>Green (proto)</u>	Rear <u>Yellow</u>
Limiters:	in mm out mm	in mm out mm
Shock Length(A):	<u>20</u> mm	<u>27</u> mm
Shock Top Type:	<input type="checkbox"/> Alu(UM719/Std)	<input type="checkbox"/> UM753-1

5.8mm Ball End:

Front: S M L

Rear: S M L

Chassis:

Ride Height:

Front 18.5 mm

Rear A B 19 mm

Tire:

	Front	Rear
Tire:	<u>Cut Stagger</u>	<u>Mini Spike</u>
Inserts:	<u>Normal</u>	<u>Normal</u>
Wheel:	<u>Normal</u>	<u>Normal</u>
Traction Compound:	_____	_____

Electronics:

Battery:
 Saddle Pack Short

Battery Position:
 Std 8mm Front

Motor Position:
 Front Rear

Motor Mount Position:
 Std 8mm Front

ORION VST PRO
LW 5.5T

Motor: _____

Pinion/Spur: 23 / 78

Body / Wing:

Body: Blade LW

Wing Mount: Narrow Wide

Wing Dum Height: 18 mm

Wing: X-GEAR

Wing Angle: 4° 7° 10°

Lip Height: 2 mm

Material:

Screw: Steel Titanium

Pinion Gear: Steel Aluminium

Shock O-Ring: O-ring X-ring Red Clear

Comment : Front&Rear Shock Stay : Proto Carbon
AXON Ball Bearing : 15x10x4, 10x5x4, 8x5x2.5
Front Wing : Azarashi